


Plaster sink and top


FITTING INSTRUCTIONS - LEG BEARERS



Please follow the installation instructions below for a sink with leg bearers

Wind the foot of the leg bearer fully in then back out 5mm.
Offer the leg bearer up to the wall in the desired position;
Note that each leg bearer is set ten millimetres in from the ends of the sink.
Mark through the holes at the back of the bearer and also the holes in the foot.
Follow the same procedure for subsequent leg bearers ensuring that all the bearers are level with the first. Use the adjustment in the foot to compensate for any discrepancies in the floor.
Drill / plug the wall and floor as appropriate for the fixings to be used (provided by others). Secure the leg bearers to the wall and floor.
Remove all packaging material from the sink.
Lower the sink into position over the leg bearers making sure all the threaded studs drop through the holes in the leg bearers. Secure the sink in place using the nuts and washers provided.
Fit the waste following the instructions enclosed with the waste.
Seal the edge of the sink adjacent to the wall as appropriate using a proprietary sealant.

FITTING INSTRUCTIONS - CANTILEVER BRACKETS



Please follow the installation instructions below for a sink with cantilever brackets

Offer the bracket up to the wall in the desired position; Note the distance to the outer edge of the brackets must be equal to the length of the sink.
Mark through the holes at the back of the bracket. Follow the same procedure for subsequent brackets ensuring that all the brackets are level with the first.
Drill / plug the wall as appropriate for the fixings to be used (provided by others).
Remove the plastic covering from the brackets and secure the brackets to the wall.
Remove all packaging material from the sink.
Lower the sink into position over the brackets making sure all the threaded studs drop through the holes in the brackets. Secure the sink in place using the nuts and washers provided.
Fit the waste following the instructions enclosed with the waste.
Seal the edge of the sink adjacent to the wall as appropriate using a proprietary sealant.

CARE OF YOUR NEW STAINLESS STEEL PRODUCT

HANDLING AND FIXING CAUTION

Take care when handling and fixing this product. Exposed edges of the stainless steel, including tap holes, upstand, overflows and wastes etc. may cause harm if handled without due caution. When using the fixing clips supplied with inset sinks avoid touching the two prongs on the area of the clip that grips the underside of the worktop.

TO THE STOCKIST

Please store products in a cool, dry area.

Sinks should, where possible be stood on their ends supported by battens with the bowl uppermost.

If sinks are nested with bowls inside one another, place some dry cushioning material between them to protect the surfaces.

TO THE INSTALLER

DO handle with care to avoid scuffs and scratches during installation.

DO check that edges of sinks are dead level so that water will flow off the draining board.

DO NOT over-tighten plumbing or other mechanical fixtures.

DO NOT remove the plastic protective film applied to certain products until all installation work has been completed.

DO NOT stand/kneel on the drainer of sinks.

DO NOT drop mortar, plaster or similar substances onto the stainless steel.

TO THE USER

Stainless steel will give you a lifetime of trouble free use as long as you follow a few simple rules. If it appears to mark, don't worry, it is usually not the steel, but something deposited on it, which has caused the apparent stain.

DO-wash the product before use.

DO-clean the product regularly, using JIF, Goddards, or similar recommended cleaners. Follow the manufacturer's instructions carefully. Always rinse well with clean water and dry the surface with a soft cloth.

DO-use nylon or bristle brushes, not metal scrapers or wire brushes to loosen stubborn stains.

Never use wire wool pads, as they can scratch the steel.

DO-take care when handling sharp objects as they can scratch the surface of the steel. Any scratches will blend together over a period of time and become less noticeable with age. There is no detriment to the corrosion resistance or general performance of the material.

DO NOT-allow undiluted bleach to remain in contact with stainless steel (remember dishwasher powders, sterilising agents and similar products all contain chlorides). Black pit marks can result and permanent damage can be caused.

Dilute to manufacturer's instructions and always rinse with clean water.

DO NOT-soak clothes in bleach solutions for long periods. Always rinse bowl with clean water after use.

DO NOT-leave such substances as Mortar, Grouting cement, soldering flux, photographic developing fluids, silver dip, denture liquids or food acids on the surface of the steel. Clean immediately and rinse well with clean water.

DO NOT-allow corrosive foodstuffs, such as fruit juices, damp salt, vinegar, mustards, pickles and mayonnaise to remain on the surface of the steel for long periods. Wash and rinse away.

DO NOT-let hard water cause a build up of lime or chalk deposits which can sometimes be seen as a greyish film. Clean regularly with recommended cleaners to avoid this problem and always wipe dry with a soft cloth.

DO NOT-worry if the steel appears to rust. Usually it's deposits of wire wool scouring pads, plumbers swarf, particles from rusting storage tanks or other deposits on the surface which can be cleaned and rinsed away following your usual cleaning procedure. Bases of washing up bowls can harbour such deposits – check regularly.

DO NOT-use coarse grit cleaners or wire wool pads when cleaning the steel. They will scratch the surface.

DO NOT-leave carbon steel objects such as bottle openers, scissors, whisks and other kitchen objects standing on the surface for long periods, they can rust and leave marks.

DO PLEASE ENJOY YOUR NEW STAINLESS STEEL PRODUCT

<u>Problem</u>	<u>Corrective Treatment</u>	<u>Comments</u>
Routine Cleaning	washing up liquid, all purpose cleaning liquid, swab with cloth or sponge rinse well and dry. For disinfection use proprietary Anti-Bacterial Non bleach	Satisfactory on all surface finishes
Oil and Grease Marks	De-greasing fluid or cellulose thinners	Rinse with soap and water
Stubborn marks stains and light discolouration	Mild abrasive creams (Sif / Shiny Sinks	Heavy scale can be loosen by soaking with Met-soak or Hi-Phos. Rinse thoroughly after soaking as these products cause rust type marks if left
Heavy discolouration or heat tint	Use Metal polish (Brasso. Goddards S/Steel Cleaner, Bar keepers Friend) or a light non metallic abrasive pad. Dura-Glit <u>Only on grained finishes not bright mat.</u>	Use only on Grain finish surfaces and work in direction of grain as slight scratching will occur
		Bleach solutions including over the counter brands must only be used in dilution as instructed and thoroughly rinse immediately after application, as chloride containing compounds will cause corrosion on all grades of stainless steel.
Lime Scale	Apply descaler as instructed agitate allow to soak remove, re-apply if not fully removed (Met-soak DX4920 or Hi-Phos)	Rinse thoroughly after application and wipe dry as rust type stains can result if left undiluted on surface

There are also products on the market which help to reduce the marks left by fingers and hands One of which is 3M's stainless steel cleaner, also of help is baby oil very lightly applied to the surface

SANITIZING URINAL BLOCKS. The use of these products must be done with the knowledge that they can in some instances react with other cleaning agents or on their own and cause scarring of the surface of the stainless steel. It is advisable to move them around the channel frequently to reduce there effect on one concentrated area