

## Application overview – Geberit Mepla

Geberit India, Version: February 2026

Application purposes	Operating temperature	Maximum operating pressure	Pipes		Fittings					O-rings	Flat gaskets for screw connections	Flange gaskets
			Mepla, multilayer pipe	MeplaTherm ML NPW	Plastic	lead-free red brass / lead-free silicon bronze	Gunmetal	Brass	Stainless steel	EPDM, black	Fibre composite material	Fibre composite material
<b>Liquid media</b>												
For cold and hot potable water	0–70 °C <sup>3)</sup>	10 bar / 1000 kPa	✓		✓	✓	✓	✓		✓	✓	✓
For cold potable water	0–20 °C	16 bar / 1600 kPa <sup>4)</sup>	✓		✓	✓	✓	✓		✓	✓	✓
For cooling and heating water without antifreeze agent	0–80 °C <sup>4)</sup>	10 bar / 1000 kPa	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
For cooling and heating water with antifreeze agent	-10 – +40 °C <sup>5)</sup>	10 bar / 1000 kPa	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
For service water and process water	0–70 °C	10 bar / 1000 kPa	7)	7)	7)	7)	7)		7)	7)	7)	7)
For treated water <sup>1)</sup>	0–70 °C	10 bar / 1000 kPa	✓ <sup>8)</sup>	✓ <sup>8)</sup>	✓ <sup>8)</sup>	✓ <sup>8)</sup>	✓ <sup>8)</sup>		✓ <sup>8)</sup>	✓ <sup>8)</sup>	✓ <sup>8)</sup>	✓ <sup>8)</sup>
For rainwater with a pH value ≥ 5.5	0–70 °C	10 bar / 1000 kPa	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
For seawater	0–70 °C	10 bar / 1000 kPa	✓	✓	✓				✓	✓	✓	✓
For chemicals and technical liquids	Upon request	Upon request	7)	7)	7)	7)	7)	7)	7)	7)	7)	7)
<b>Gaseous media</b>												
For compressed air (oil purity class 0–3)	0–70 °C	10 bar / 1000 kPa	✓	✓	✓	✓	✓	✓	✓	✓ <sup>9)</sup>	✓	✓
For negative pressure <sup>2)</sup>	0–70 °C	Abs. ≥ 0.2 bar / 20 kPa	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

✓ Application generally approved if the defined additional requirements are met in accordance with the footnotes

<sup>1)</sup> Range of application according to Technical Information (TI) "Treated waters"

<sup>2)</sup> Usable negative pressure for Geberit piping systems:

The usable negative pressure is calculated on the basis of the air pressure at the place of installation minus the absolute pressure of 200 mbar.

Example: 980 mbar air pressure – 200 mbar absolute pressure = 780 mbar usable negative pressure in the piping system

<sup>3)</sup> Malfunction temperature in accordance with EN 806-2: Tmal = 95 °C, total 100 h over the course of the service life

<sup>4)</sup> Malfunction temperature in accordance with ISO 10508:2006: Tmal = 100 °C, total 100 h over the course of the service life

<sup>5)</sup> Higher temperatures after Geberit approval only

<sup>6)</sup> 10 bar/1000 kPa for MasterFix and MeplaFix

<sup>7)</sup> Following Geberit approval

<sup>8)</sup> Application range according to TI "Treated Waters"

<sup>9)</sup> Oil purity class in accordance with ISO 8573-1:2010E; for details on moisture and particles, see Technical Information "Geberit Piping Systems for Compressed Air Installations"



- The operating conditions specified in the relevant approvals, standards and technical regulations must be observed for each application. These may deviate from the aforementioned specifications