

Afmetingveranderingen Geberit Mapress rvs 2021

		arc / hoek (°)	d, ø	D	La	L	L1	L2	H	Z
Geberit Mapress rvs axiale compensator met persmoffen	33941		108 mm	13.7 cm	+ - 23 cm	31.6 cm				
Geberit Mapress rvs sok	32009		76.1 mm			12.7 cm				2.1 cm
	32010		88.9 mm			14.5 cm				2.5 cm
	32011		108 mm			17.6 cm				2.6 cm
Geberit Mapress rvs sok (gas)	34248		76.1 mm			12.7 cm				2.1 cm
	34249		88.9 mm			14.5 cm				2.5 cm
	34250		108 mm			17.6 cm				2.6 cm
Geberit Mapress rvs sok (LABS-vrij)	82009		76.1 mm			12.7 cm				2.1 cm
	82010		88.9 mm			14.5 cm				2.5 cm
	82011		108 mm			17.6 cm				2.6 cm
Geberit Mapress rvs sok (FKM blauw)	50071		76.1 mm			12.7 cm				2.1 cm
	50072		88.9 mm			14.5 cm				2.5 cm
	50073		108 mm			17.6 cm				2.6 cm
Geberit Mapress rvs bocht	30105	90°	28 mm			5.7 cm				3.4 cm
	34003	90°	28 mm			5.7 cm				3.4 cm
	80105	90°	28 mm			5.7 cm				3.4 cm
	50285	90°	28 mm			5.7 cm				3.4 cm
Geberit Mapress rvs bocht met insteekende	30305	90°	28 mm			5.7 cm		6.3 cm		3.4 cm
	34010	90°	28 mm			5.7 cm		6.3 cm		3.4 cm
	80305	90°	28 mm			5.7 cm		6.3 cm		3.4 cm
	50315	90°	28 mm			5.7 cm		6.3 cm		3.4 cm
Geberit Mapress rvs bocht	30601	45°	12 mm			2.3 cm				0.6 cm
	30602	45°	15 mm			2.8 cm				0.8 cm
	30603	45°	18 mm			2.9 cm				0.9 cm
	30604	45°	22 mm			3.2 cm				1.1 cm
	30605	45°	28 mm			3.7 cm				1.4 cm
	30605	45°	28 mm			3.7 cm				1.4 cm
	32606	45°	35 mm			4.3 cm				1.7 cm
	32607	45°	42 mm			5.1 cm				2.1 cm
	32608	45°	54 mm			6.2 cm				2.7 cm
	34014	45°	15 mm			2.8 cm				0.8 cm
	34015	45°	18 mm			2.9 cm				0.9 cm
	34016	45°	22 mm			3.2 cm				1.1 cm
	34017	45°	28 mm			3.7 cm				1.4 cm
	34193	45°	35 mm			4.3 cm				1.7 cm
	34194	45°	42 mm			5.1 cm				2.1 cm
	34195	45°	54 mm			6.2 cm				2.7 cm
	80602	45°	15 mm			2.8 cm				0.8 cm
	80603	45°	18 mm			2.9 cm				0.9 cm
	80604	45°	22 mm			3.2 cm				1.1 cm
	80605	45°	28 mm			3.7 cm				1.4 cm
	82606	45°	35 mm			4.3 cm				1.7 cm
	82607	45°	42 mm			5.1 cm				2.1 cm
	82608	45°	54 mm			6.2 cm				2.7 cm
	50222	45°	15 mm			2.8 cm				0.8 cm
	50223	45°	18 mm			2.9 cm				0.9 cm
	50224	45°	22 mm			3.2 cm				1.1 cm
	50225	45°	28 mm			3.7 cm				1.4 cm
	50226	45°	35 mm			4.3 cm				1.7 cm
	50227	45°	42 mm			5.1 cm				2.1 cm
	50228	45°	54 mm			6.2 cm				2.7 cm

